
Django REST Framework JSON API Documentation

Release 2.0.0-alpha.1

Jerel Unruh

Apr 21, 2017

Contents

1	Getting Started	3
1.1	Requirements	4
1.2	Installation	4
1.3	Running the example app	4
1.4	Running Tests	4
2	Usage	5
2.1	Configuration	5
2.2	Serializers	6
2.3	Setting the resource_name	6
2.4	Inflecting object and relation keys	6
2.5	Related fields	9
2.6	RelationshipView	11
2.7	Meta	11
2.8	Links	12
2.9	Included	12
3	API	15
3.1	mixins	15
3.2	rest_framework_json_api.renderers.JSONRenderer	15
3.3	rest_framework_json_api.parsers.JSONParser	16
4	Indices and tables	17

Contents:

CHAPTER 1

Getting Started

Note: this package is named Django REST Framework JSON API to follow the naming convention of other Django REST Framework packages. Since that's quite a bit to say or type this package will be referred to as DJA elsewhere in these docs.

By default, Django REST Framework produces a response like:

```
{
  "count": 20,
  "next": "http://example.com/api/1.0/identities/?page=3",
  "previous": "http://example.com/api/1.0/identities/?page=1",
  "results": [{
    "id": 3,
    "username": "john",
    "full_name": "John Coltrane"
  }]
}
```

However, for the same `identity` model in JSON API format the response should look like the following:

```
{
  "links": {
    "first": "http://example.com/api/1.0/identities",
    "last": "http://example.com/api/1.0/identities?page=5",
    "next": "http://example.com/api/1.0/identities?page=3",
    "prev": "http://example.com/api/1.0/identities",
  },
  "data": [{
    "type": "identities",
    "id": 3,
    "attributes": {
      "username": "john",
      "full-name": "John Coltrane"
    }
  }],
  "meta": {
```

```
        "pagination": {
            "page": "2",
            "pages": "5",
            "count": "20"
        }
    }
}
```

Requirements

1. Python \geq 2.7
2. Django
3. Django REST Framework \geq 3.1

Installation

From PyPI

```
pip install djangoestframework-jsonapi==2.0.0-beta.1
```

From Source

```
git clone https://github.com/django-json-api/django-rest-framework-json-api.git
cd django-rest-framework-json-api && pip install -e .
```

Running the example app

```
git clone https://github.com/django-json-api/django-rest-framework-json-api.git
cd django-rest-framework-json-api && pip install -e .
django-admin.py runserver
```

Browse to <http://localhost:8000>

Running Tests

```
python runtests.py
```


CHAPTER 2

Usage

The DJA package implements a custom renderer, parser, exception handler, and pagination. To get started enable the pieces in `settings.py` that you want to use.

Many features of the JSON:API format standard have been implemented using Mixin classes in `serializers.py`. The easiest way to make use of those features is to import `ModelSerializer` variants from `rest_framework_json_api` instead of the usual `rest_framework`

Configuration

We suggest that you copy the settings block below and modify it if necessary.

```
REST_FRAMEWORK = {
    'PAGE_SIZE': 10,
    'EXCEPTION_HANDLER': 'rest_framework_json_api.exceptions.exception_handler',
    'DEFAULT_PAGINATION_CLASS':
        'rest_framework_json_api.pagination.PageNumberPagination',
    'DEFAULT_PARSER_CLASSES': (
        'rest_framework_json_api.parsers.JSONParser',
        'rest_framework.parsers.FormParser',
        'rest_framework.parsers.MultiPartParser'
    ),
    'DEFAULT_RENDERER_CLASSES': (
        'rest_framework_json_api.renderers.JSONRenderer',
        'rest_framework.renderers.BrowsableAPIRenderer',
    ),
    'DEFAULT_METADATA_CLASS': 'rest_framework_json_api.metadata.JSONAPIMetadata',
}
```

If `PAGE_SIZE` is set the renderer will return a meta object with record count and a links object with the next, previous, first, and last links. Pages can be selected with the page GET parameter. The query parameter used to retrieve the page can be customized by subclassing `PageNumberPagination` and overriding the `page_query_param`. Page size can be controlled per request via the `PAGINATE_BY_PARAM` query parameter (`page_size` by default).

Serializers

It is recommended to import the base serializer classes from this package rather than from vanilla DRF. For example,

```
from rest_framework_json_api import serializers

class MyModelSerializer(serializers.ModelSerializer):
    # ...
```

Setting the resource_name

You may manually set the `resource_name` property on views, serializers, or models to specify the `type` key in the json output. In the case of setting the `resource_name` property for models you must include the property inside a `JSONAPIMeta` class on the model. It is automatically set for you as the plural of the view or model name except on resources that do not subclass `rest_framework.viewsets.ModelViewSet`:

Example - `resource_name` on View:

```
class Me(generics.GenericAPIView):
    """
    Current user's identity endpoint.

    GET /me
    """
    resource_name = 'users'
    serializer_class = identity_serializers.IdentitySerializer
    allowed_methods = ['GET']
    permission_classes = (permissions.IsAuthenticated, )
```

If you set the `resource_name` property on the object to `False` the data will be returned without modification.

Example - `resource_name` on Model:

```
class Me(models.Model):
    """
    A simple model
    """
    name = models.CharField(max_length=100)

    class JSONAPIMeta:
        resource_name = "users"
```

If you set the `resource_name` on a combination of model, serializer, or view in the same hierarchy, the name will be resolved as following: view > serializer > model. (Ex: A view `resource_name` will always override a `resource_name` specified on a serializer or model). Setting the `resource_name` on the view should be used sparingly as serializers and models are shared between multiple endpoints. Setting the `resource_name` on views may result in a different `type` being set depending on which endpoint the resource is fetched from.

Inflecting object and relation keys

This package includes the ability (off by default) to automatically convert json requests and responses from the python/rest_framework's preferred underscore to a format of your choice. To hook this up include the following setting in your project settings:

```
JSON_API_FORMAT_KEYS = 'dasherize'
```

Possible values:

- dasherize
- camelize (first letter is lowercase)
- capitalize (camelize but with first letter uppercase)
- underscore

Note: due to the way the inflector works `address_1` can camelize to `address1` on output but it cannot convert `address1` back to `address_1` on POST or PUT. Keep this in mind when naming fields with numbers in them.

Example - Without format conversion:

```
{
  "data": [{
    "type": "identities",
    "id": 3,
    "attributes": {
      "username": "john",
      "first_name": "John",
      "last_name": "Coltrane",
      "full_name": "John Coltrane"
    }
  ]},
  "meta": {
    "pagination": {
      "count": 20
    }
  }
}
```

Example - With format conversion set to dasherize:

```
{
  "data": [{
    "type": "identities",
    "id": 3,
    "attributes": {
      "username": "john",
      "first-name": "John",
      "last-name": "Coltrane",
      "full-name": "John Coltrane"
    }
  ]},
  "meta": {
    "pagination": {
      "count": 20
    }
  }
}
```

Types

A similar option to `JSON_API_FORMAT_KEYS` can be set for the types:

```
JSON_API_FORMAT_TYPES = 'dasherize'
```

Example without format conversion:

```
{
  "data": [{
    "type": "blog_identity",
    "id": 3,
    "attributes": {
      ...
    },
    "relationships": {
      "home_town": {
        "data": [{
          "type": "home_town",
          "id": 3
        }]
      }
    }
  }]
}
```

When set to dasherize:

```
{
  "data": [{
    "type": "blog-identity",
    "id": 3,
    "attributes": {
      ...
    },
    "relationships": {
      "home_town": {
        "data": [{
          "type": "home-town",
          "id": 3
        }]
      }
    }
  }]
}
```

It is also possible to pluralize the types like so:

```
JSON_API_PLURALIZE_TYPES = True
```

Example without pluralization:

```
{
  "data": [{
    "type": "identity",
    "id": 3,
    "attributes": {
      ...
    },
    "relationships": {
      "home_towns": {
        "data": [{

```

```

        "type": "home_town",
        "id": 3
    }}
}

```

When set to pluralize:

```

{
  "data": [{
    "type": "identities",
    "id": 3,
    "attributes": {
      ...
    },
    "relationships": {
      "home_towns": {
        "data": [{
          "type": "home_towns",
          "id": 3
        }]
      }
    }
  }]
}

```

Related fields

Because of the additional structure needed to represent relationships in JSON API, this package provides the `ResourceRelatedField` for serializers, which works similarly to `PrimaryKeyRelatedField`. By default, `rest_framework_json_api.serializers.ModelSerializer` will use this for related fields automatically. It can be instantiated explicitly as in the following example:

```

from rest_framework_json_api import serializers
from rest_framework_json_api.relations import ResourceRelatedField

from myapp.models import Order, LineItem, Customer

class OrderSerializer(serializers.ModelSerializer):
    class Meta:
        model = Order

    line_items = ResourceRelatedField(
        queryset=LineItem.objects,
        many=True # necessary for M2M fields & reverse FK fields
    )

    customer = ResourceRelatedField(
        queryset=Customer.objects # queryset argument is required
                                # except when read_only=True
    )

```

In the [JSON API spec](#), relationship objects contain links to related objects. To make this work on a serializer we need to tell the `ResourceRelatedField` about the corresponding view. Use the `HyperlinkedModelSerializer` and instantiate the `ResourceRelatedField` with the relevant keyword arguments:

```
from rest_framework_json_api import serializers
from rest_framework_json_api.relations import ResourceRelatedField

from myapp.models import Order, LineItem, Customer

class OrderSerializer(serializers.HyperlinkedModelSerializer):
    class Meta:
        model = Order

        line_items = ResourceRelatedField(
            queryset=LineItem.objects,
            many=True,
            related_link_view_name='order-lineitems-list',
            related_link_url_kwarg='order_pk',
            self_link_view_name='order-relationships'
        )

        customer = ResourceRelatedField(
            queryset=Customer.objects,
            related_link_view_name='order-customer-detail',
            related_link_url_kwarg='order_pk',
            self_link_view_name='order-relationships'
        )
```

- `related_link_view_name` is the name of the route for the related view.
- `related_link_url_kwarg` is the keyword argument that will be passed to the view that identifies the ‘parent’ object, so that the results can be filtered to show only those objects related to the ‘parent’.
- `self_link_view_name` is the name of the route for the `RelationshipView` (see below).

In this example, `reverse('order-lineitems-list', kwargs={'order_pk': 3})` should resolve to something like `/orders/3/lineitems`, and that route should instantiate a view or viewset for `LineItem` objects that accepts a keyword argument `order_pk`. The [drf-nested-routers](#) package is useful for defining such nested routes in your `urlpatterns`.

The corresponding viewset for the `line-items-list` route in the above example might look like the following. Note that in the typical use case this would be the same viewset used for the `/lineitems` endpoints; when accessed through the nested route `/orders/<order_pk>/lineitems` the `queryset` is filtered using the `order_pk` keyword argument to include only the `lineitems` related to the specified order.

```
from rest_framework import viewsets

from myapp.models import LineItem
from myapp.serializers import LineItemSerializer

class LineItemViewSet(viewsets.ModelViewSet):
    queryset = LineItem.objects
    serializer_class = LineItemSerializer

    def get_queryset(self):
        queryset = self.queryset
```

```
# if this viewset is accessed via the 'order-lineitems-list' route,
# it will have been passed the 'order_pk' kwarg and the queryset
# needs to be filtered accordingly; if it was accessed via the
# unnested '/lineitems' route, the queryset should include all LineItems
if 'order_pk' in self.kwargs:
    order_pk = self.kwargs['order_pk']
    queryset = queryset.filter(order__pk=order_pk)

return queryset
```

RelationshipView

`rest_framework_json_api.views.RelationshipView` is used to build relationship views (see the [JSON API spec](#)). The self link on a relationship object should point to the corresponding relationship view.

The relationship view is fairly simple because it only serializes [Resource Identifier Objects](#) rather than full resource objects. In most cases the following is sufficient:

```
from rest_framework_json_api.views import RelationshipView

from myapp.models import Order

class OrderRelationshipView(RelationshipView):
    queryset = Order.objects
```

The `urlconf` would need to contain a route like the following:

```
url(
    regex=r'^orders/(?P<pk>[^\./]+)/relationships/(?P<related_field>[^\./]+)$',
    view=OrderRelationshipView.as_view(),
    name='order-relationships'
)
```

The `related_field` kwarg specifies which relationship to use, so if we are interested in the relationship represented by the related model field `Order.line_items` on the `Order` with pk 3, the url would be `/order/3/relationships/line_items`. On `HyperlinkedModelSerializer`, the `ResourceRelatedField` will construct the url based on the provided `self_link_view_name` keyword argument, which should match the `name=` provided in the `urlconf`, and will use the name of the field for the `related_field` kwarg. Also we can override `related_field` in the url. Let's say we want the url to be: `/order/3/relationships/order_items` - all we need to do is just add `field_name_mapping` dict to the class:

```
field_name_mapping = {
    'line_items': 'order_items'
}
```

Meta

You may add metadata to the rendered json in two different ways: `meta_fields` and `get_root_meta`.

On any `rest_framework_json_api.serializers.ModelSerializer` you may add a `meta_fields` property to the `Meta` class. This behaves in the same manner as the default `fields` property and will cause

SerializerMethodFields or model values to be added to the `meta` object within the same data as the serializer.

To add metadata to the top level `meta` object add:

```
def get_root_meta(self, resource, many):
    if many:
        # Dealing with a list request
        return {
            'size': len(resource)
        }
    else:
        # Dealing with a detail request
        return {
            'foo': 'bar'
        }
```

to the serializer. It must return a dict and will be merged with the existing top level `meta`.

To access metadata in incoming requests, the `JSONParser` will add the metadata under a top level `_meta` key in the parsed data dictionary. For instance, to access meta data from a serializer object, you may use `serializer.initial_data.get("_meta")`. To customize the `_meta` key, see [here](#).

Links

Adding `url` to fields on a serializer will add a `self` link to the `links` key.

Related links will be created automatically when using the Relationship View.

Included

JSON API can include additional resources in a single network request. The specification refers to this feature as [Compound Documents](#). Compound Documents can reduce the number of network requests which can lead to a better performing web application. To accomplish this, the specification permits a top level `included` key. The list of content within this key are the extra resources that are related to the primary resource.

To make a Compound Document, you need to modify your `ModelSerializer`. The two required additions are `included_resources` and `included_serializers`.

For example, suppose you are making an app to go on quests, and you would like to fetch your chosen knight along with the quest. You could accomplish that with:

```
class KnightSerializer(serializers.ModelSerializer):
    class Meta:
        model = Knight
        fields = ('id', 'name', 'strength', 'dexterity', 'charisma')

class QuestSerializer(serializers.ModelSerializer):
    included_serializers = {
        'knight': KnightSerializer,
    }

    class Meta:
        model = Quest
```



```
fields = ('id', 'title', 'reward', 'knight')

class JSONAPIMeta:
    included_resources = ['knight']
```

`included_resources` informs DJA of **what** you would like to include. `included_serializers` tells DJA **how** you want to include it.

mixins

MultipleIDMixin

Add this mixin to a view to override `get_queryset` to automatically filter records by `ids[]=1&ids[]=2` in URL query params.

rest_framework_json_api.renderers.JSONRenderer

The `JSONRenderer` exposes a number of methods that you may override if you need highly custom rendering control.

extract_attributes

```
extract_attributes(fields, resource)
```

Builds the `attributes` object of the JSON API resource object.

extract_relationships

```
extract_relationships(fields, resource, resource_instance)
```

Builds the `relationships` top level object based on related serializers.

extract_included

```
extract_included(fields, resource, resource_instance, included_resources)
```

Adds related data to the top level `included` key when the request includes `?include=example,example_field2`

extract_meta

```
extract_meta(serializer, resource)
```

Gathers the data from serializer fields specified in `meta_fields` and adds it to the `meta` object.

extract_root_meta

```
extract_root_meta(serializer, resource)
```

Calls a `get_root_meta` function on a serializer, if it exists.

build_json_resource_obj

```
build_json_resource_obj(fields, resource, resource_instance, resource_name)
```

Builds the resource object (type, id, attributes) and extracts relationships.

rest_framework_json_api.parsers.JSONParser

Similar to `JSONRenderer`, the `JSONParser` you may override the following methods if you need highly custom parsing control.

parse_metadata

```
parse_metadata(result)
```

Returns a dictionary which will be merged into parsed data of the request. By default, it reads the `meta` content in the request body and returns it in a dictionary with a `_meta` top level key.

CHAPTER 4

Indices and tables

- `genindex`
- `search`